








AT28C256: Package Marking Information (SMD devices)

28-pin CERDIP		32-pad CLCC	
Topside	Backside	Topside	Backside
 ATMEL 5962-88525 ##XA C AT28C256@ %%DM/883 YQyyww1	 ●YWWNNN-19104S 1&&&&&- YYWW	 ATMEL 5962-88525 ##YA YQyyww1 AT28C256@ %%LM/883 C	 YWWNNNS 19104 1&&&&&- YYWW
28-lead FLATPACK		30-pin PGA	
Topside	Backside	Topside	Edges
 ATMEL 5962-88525 ##ZA C AT28C256@ %%FM/883 YQyyww1	 ●YWWNNN-19104S 1&&&&&- YYWW	 ATMEL 5962-88525 ##UA YQyyww1 AT28C256@ %%UM/883 C	1&&&&&- YYWW YQNNNN-19104S

## = SMD Device 03: 250 ns, SDP off 04: 200 ns, SDP off 06: 150 ns, SDP off 11: 250 ns, SDP on 12: 200 ns, SDP on 14: 150 ns, SDP on	%% = Access Time 25: 250 ns 20: 200 ns 15: 150 ns	@ = Write Endurance Rating Blank: Standard (10K at 10ms) E: Extended (100K at 10ms) F: Fast Write (10k at 3ms)	\$ = Assembly Location F: Philippines N: Thailand
Country of Assembly &&&&&: Country of Assembly	Lot Trace Code YWWNNN: Lot Trace Code	Seal Year and Work Week YYWW: Seal Year and Work Week	
Year, Quarter, Seal Year, Seal Week and Group D Coverage (Military Date Code)			
YQyyww1: Year, Quarter, Seal Year, Seal Week and Group D Coverage (Military Date Code)			